



## SPECIFICATIONS

<b>General</b>	PIM Shield Cable Support Rails provide a low passive intermodulation mounting system to secure multiple Cable Support Blocks (sold separately) in high risk PIM zones. The Pole Mount Kit includes one rail plus the hardware required to secure the rail to a pole. An Extra Rail Kit can be added (sold separately) to double the number of connection points.
<b>Grip range</b>	2.37-inch to 4.5-inch OD pipe (2-inch to 4-inch nominal pipe)
<b>Rail dimensions</b>	24.0-inch x 1.5-inch x 1.5-inch
<b>Pole mounting hardware</b>	3/8-16 UNC, Galvanized steel
<b>Rail attachment hardware</b>	M10-1.5, Galvanized steel
<b>System PIM performance</b>	IM3 <-100 dBm when tested in accordance with proposed IEC 62037-8, near field test, 2x 20W test tones, while subjected to dynamic stimulus. To achieve specified PIM performance, torque all 3/8-inch hardware to 10 FT-LB and all M10 hardware to 15 FT-LB. (ConcealFab tools 900053 and 900412)
<b>Rail Material</b>	Extruded aluminum with clear anodize finish
<b>Pole bracket material</b>	Galvanized steel
<b>Operating temperature</b>	-40°C to +70°C
<b>Case dimensions</b>	25.0-inch x 11.0-inch x 6.0-inch
<b>Case weight</b>	46 lb.
<b>Qty per case</b>	10