



NSG 434 ESD SIMULATOR **BASIC PERFORMANCE IN A COMPACT DESIGN**



- **Programmable discharge voltage 200 V to 8.8 kV**
- **Stabilized charging voltage**
- **Pre-programmed IEC/EN 61000-4-2 test settings up to level 3**
- **True air-discharge breakdown voltage**
- **Battery powered**
- **Compact and lightweight design**
- **Comfortable use and convenient operation**

Ergonomic design and advanced functionality. The pistol-shaped NSG 434 simulator is designed to sit comfortably in the operator's hand, with current operating conditions constantly displayed and clearly visible.

NSG 434's microprocessor-based controller and multifunction keypad provide the operator with instant access to its comprehensive range of built-in functions. The LCD panel continuously displays the operating status and all user-selected test parameters.

NSG 434 has its own internal, battery operated high voltage generator. In addition to the pre-programmed, standard IEC pulses, the user can create custom tests using single or repetitive discharges with selectable rates and manual or automatic polarity switching. An optional mains supply is available for extended test operation or for use when the battery is being charged.

NSG 434 measures and displays true air breakdown voltages. It also detects real or valid air-discharges, thereby avoiding misleading discharge counts. This is especially important during long term tests and remote test setups.

A range of interchangeable discharge networks is available, including EN, ANSI-IEEE, and ISO. The unit comes with a standard 150 pF/330 Ω discharge network for tests to IEC/EN 61000-4-2.

NSG 434 is supplied with standard accessories, including interchangeable test tips, a grounding cable and battery charger - all in a durable carrying case. There is an optional fiber optic remote control trigger for operation inside a screened room or enclosure. The LCD panel gives the operator a clear, continuous indication of all the test parameters, the operational status of the instrument and the current function of each of the five softkeys.

NSG 434 ESD SIMULATOR

BASIC PERFORMANCE IN A COMPACT DESIGN

Technical specifications

Basic set:	Carrying case with: electrostatic discharge simulator, battery pack, battery charger 100 to 240 VAC, discharge network 150 pF/330 Ω , air- and contact-discharge tips, grounding cable, user manual
Pulse network:	Network 150 pF/330 Ω as per IEC/EN 61000-4-2 (included) Range of R/C networks for other standards: R = 0 Ω to 10 k Ω ; C = 60 to 500 pF
Discharge voltage:	Air-discharge: 200 V to 8.8 kV (in 100 V steps) Contact-discharge: 200 V to 6.6 kV (in 100 V steps)
Discharge tips:	Ball and point as per IEC
Charging voltage measurement:	kV, accuracy better than $\pm 5\%$ (stabilized); measurement and display of true air flashover voltage
Discharge detection:	Indicated by an oval around the kV symbol, also acoustically in the 'Single' operating mode (air-discharge only)
Holding time:	>5 s (charging voltage ... $\pm 5\%$)
Polarity:	Positive / negative / automatic change
Operating modes:	Single / repetitive = pulse counter: 0 to 9999, preselect counter 0 to 9999 Repetition: 0.5/1/5/10/20 or 25 Hz (air); 0.5/1/5 or 10 Hz (contact); continuous operation
Display:	LCD panel showing: charging voltage, discharge voltage, polarity, air-/contact-discharge, counter/preselect counter content, soft-key functions, battery monitor
Weight:	NSG 434 with battery: 1.2 kg (2.6 lbs) approx.
Ambient conditions:	Operation: +5 to +40°C, 20 to 80 % r.h. (non-condensing), 68 to 106 kPa

Ordering information

NSG 434	NSG 434 ESD simulator - basic set as per technical specifications
Accessories:	
INA 420	Fast risetime test tip <400 ps
INA 421	Network and test tip for IEC 801-2 (1984), 150 pF/150 Ω
MD 101	ESD measurement target conforming to IEC/EN 61000-4-2 (2001)
MD 103	ESD measurement target (ANSI and IEC draft)
INA 402-x	Mains power supply (80 to 240 V, 50/60 Hz) incl. grip adapter
INA 405	Spare battery pack
INA 415	Remote triggering unit including 5 m opto-cable
INA xxx	Special discharge networks (specify values of R and C)

Teseq AG

Nordstrasse 11F 4542 Luterbach Switzerland
T +41 32 681 40 40 F +41 32 681 40 48
sales@teseq.com www.teseq.com

© February 2011 Teseq®

Specifications subject to change without notice. Teseq® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, Teseq® does not assume any liability for errors or inaccuracies.

691-184A February 2011

TESEQ

Advanced Test Solutions for EMC